



LEGEND

- ①— AGGREGATE BASE COURSE, 10", ITEM 304.
- ②— BITUMINOUS PRIME COAT, ITEM 408, 1/2 GALLON PER SQUARE YARD TO BE APPLIED IMMEDIATELY UPON COMPLETION OF THE AGGREGATE BASE.
- ③— ASPHALT CONCRETE, ITEM 403, 1" COURSE TO BE APPLIED NO SOONER THAN 5 DAYS AFTER APPLICATION OF PRIME COAT.
- ④— BITUMINOUS TACK COAT, ITEM 407, 0.1 GALLON PER SQUARE YARD TO BE APPLIED PRIOR TO THE 2" FINISH COURSE OF ASPHALT.
- ⑤— ASPHALT CONCRETE, ITEM 404, 2" COURSE TO BE APPLIED AFTER A WAITING PERIOD OF NOT LESS THAN 9 MONTHS AFTER THE FIRST 1" COURSE.

NOTE A:
4'-0" NORMAL FOR RESIDENTIAL DISTRICTS,
5'-0" ON STREETS WITH 60' RIGHT-OF-WAY
OR OVER.

TYPICAL SECTION
FOR
ASPHALT PAVEMENT
ON GRAVEL BASE COURSE
SHOWING SIDEWALK AND CUT
AND FILL AREAS
(RESIDENTIAL)
NO SCALE

REVISIONS

STANDARDS FOR
PLAT CONSTRUCTION
STREET IMPROVEMENTS
IN FULL
STREET DEDICATIONS
CITY OF DAYTON, OHIO
NO SCALE 14A-17113